

aspire®

Feedlink Revvo Kit User Manual

Read this information leaflet fully before you start using this product as it contains important information. The notes below relate to when the device is filled with liquid that contains nicotine.

This product is intended for adult smokers. This product is not recommended for non-smokers, young people under the age of 18 years, pregnant or breast feeding women and those experiencing general ill health.



Contents:

- 1* Feedlink mod
- 1* 2ml Revvo Boost tank
- 2* Coils (0.10-0.14Ω)
- 1* Glass tube
- 11* O-rings
- 2* Warning card
- 1* User manual
- 1* Warranty card

Tank Features

- Bottom fill (fill through the Squonk pin)
- Adjustable airflow
- 2ml capacity
- Innovative ARC(Aspire Radial Coil) technology
- Coil resistance 0.1-0.14Ω
- Wattage range: 70-80W
- Diameter: 24mm
- Length: 41mm

Filling

Squeeze the ejuice bottle inside of the mod to fill the tank.



Coil installation

1. Unscrew and remove the top chamber.
2. Unscrew and remove the mounting screw.
3. Remove the used ARC coil by lifting over the metal pin.
4. Place a new coil over the metal pin, make sure the coil edge is lined up with the tank.
5. Screw the mounting screw back onto the base hardware.
6. Replace the top chamber.


NB: the mounting screw also acts as a 'spit-back' guard.

1



Replacing glass

1. Unscrew and remove the glass securing ring from the base hardware.
2. Pull and remove the used glass tube.
3. Insert a new glass tube.
4. Screw the glass securing ring back onto the base hardware.



Feedlink mod specifications

Output voltage: 3.0-4.2V

Resistance parameter: 0.1-3.5ohm

Modes: Bypass output

Non-adjustable Wattage/ Voltage

Battery type: Single 18650 high rate discharge battery (discharge rate ≥35A)

Continuous firing time: 10 seconds

Silicone bottle capacity: 7ml

Safety features

- **Automatic cutoff:** The continuous fire time is 10 seconds, after 10 seconds of continuous firing the mod will stop firing and the LED light under the fire button will flash 10 times.
- **Battery reverse protection**
- **Short circuit protection:** When the mod detects a short, the LED light will flash 2 or 3 times.
- **Over discharge protection:** When the battery level is below 3.2V, pressing the fire button the orange light will flash 15 times.
- **Over heat protection:** When the temperature of the control board is above 75 degree Celsius, the mod will shut off and the LED light will light up blue and orange for 3 seconds.

2

Operating instructions

1. Installing an 18650 battery into the mod, the LED light will flash blue and orange 2 times.
2. When the battery level is above 3.8V, the LED light will be blue only, when the battery level is between 3.5V and 3.8V, the light will be a mixed color of blue and orange; the orange light means the battery level is below 3.5V.
3. Click the fire button 5 times rapidly to lock or unlock the device the LED light will flash blue and orange 3 times to indicate lock or unlock. When the mod is unlocked, pressing the fire button the blue or orange LED light will light up according to the battery level.

Silicone e-juice bottle installation

- Lightly push in the bottle securing cap at the bottom of the mod.
- Then twist counter-clockwise direction to remove the securing cap.
- Insert a new silicone e-juice bottle into the plastic carrier frame, reinsert the frame into the mod then push the knob and twist clockwise direction to secure.



How to fill the Silicone e-juice bottle?

1. Unscrew and remove the metal cap at the top of the bottle.
2. Add your preferred e-juice into the bottle.
3. Replace metal cap.



3

Battery installation

1. Invert the Feedlink mod and unscrew the battery cap.
2. Insert an 18650 battery into the battery compartment with positive end pointing down and negative end pointing up.
3. Screw the battery cap back onto the mod.



IMPORTANT INFORMATION ABOUT USING NICOTINE CONTAINING E-LIQUIDS

Before using nicotine containing e-liquids the user should read the following information carefully.

NICOTINE CONTAINING E-LIQUIDS:

Do not use if you are allergic to nicotine or any of the other ingredients contained within the e-liquid (see manufacturer's label for full details).

WARNINGS AND PRECAUTIONS

Nicotine containing e-liquids are not recommended for:

- Non-smokers
- Young people under the age of 18 years;
- Pregnant or breast feeding women; as nicotine is known to cross the placenta and to be excreted in breast milk;
- Those experiencing general ill health; such as heart disease, stomach and duodenal ulcers, liver or kidney problems, long term throat disease or difficulty breathing due to bronchitis, emphysema or asthma;
- Those who have an overactive thyroid gland or have a phaeochromocytoma (a tumour of the adrenal gland that can affect high blood pressure);
- Those who have diabetes, as nicotine may affect your blood sugar levels.
- Those taking the following medication;
- Theophylline (to treat breathing problems)
- Ropinirole (to treat restless leg syndrome)
- Clozapine (to treat schizophrenia)

4

POSSIBLE SIDE EFFECTS

If you inhale too much nicotine or use the product too much you may experience one or more of the following effects:

- Feeling faint;
- Nausea (feeling sick)
- Headache
- Coughing
- Irritation of the mouth or throat
- Dizziness
- Stomach discomfort
- Hiccups
- Nasal congestion
- Vomiting (being sick)
- Heart palpitations
- Abnormal heart rate

If you experience any of these side effects; including any possible side effects not listed in this leaflet, discontinue using the product, if the effect(s) continue after you stop use, consult your doctor or healthcare professional and bring this leaflet to their attention.

To learn more about your products and how to use, please visit: www.aspirecig.com

Shenzhen Eigate Technology Co., Ltd.

Building 3, Xinhongtai Industrial Park, 14 Jian'an Rd, Tangwei, Fuyong Town, Bao'an District, Shenzhen, China
Tel: +86-755-81499783 Email: service@aspirecig.com

Manufactured By Eigate

MADE IN CHINA



5